

GetSubIdStatistics

This method is used to generate a detailed SubID statistics for a specified publisher.

Live data web services: <https://api.affili.net/V2.0/PublisherStatistics.svc?wsdl>

Demo data web services: <https://developer-api.affili.net/V2.0/PublisherStatistics.svc?wsdl>

.1 Parameters

Parameter	Type	Description
CredentialToken *	String	The authentication token you receive from the method "Logon"
StartDate *	DateTime	This parameter defines the start date for which the statistics ought to be generated. It is included in the evaluation
EndDate *	DateTime	This parameter defines the end date for which the statistics ought to be generated. It is included in the evaluation
SubId *	String	<p>This parameter specifies the SubID for which the statistics ought to be generated. Possible values are:</p> <ul style="list-style-type: none"> • "": if no value is assigned, the SubId parameter is ignored • SubId: records in which the SubID is exactly the assigned value are returned • %SubId%: records which contain the assigned value in its SubID are returned • %SubId: records in which the SubID ends with the assigned value are returned • SubId%: records in which the SubID begins with the assigned value are returned
ValuationType *	Enumeration	<p>This parameter defines the event on which the valuation should be based on. Possible values are:</p> <ul style="list-style-type: none"> • DateOfRegistration • DateOfConfirmation

ProgramIds *	Array of integer	This parameter defines the program IDs for which the sub ID statistics ought to be generated
MaximumRecords *	Integer	The maximum amount of results you want to receive
ProgramTypes *	Enumeration	This parameter defines the commission type of the requested statistics. Possible values are: <ul style="list-style-type: none"> • None • PayPerClick • PayPerSaleLead • CombinedProgram
TransactionStatus *	Enumeration	Depicts the status of the sale or lead. Possible values are: <ul style="list-style-type: none"> • Open • Confirmed • Cancelled • All

.2 Return Types

SubIdStatisticsRecords

Property	Type	Description
TotalPayment	Decimal	The total amount of money earned with this SubID
TotalPrice	Decimal	If a sale was done on the advertiser's platform, this is the value of the sale
Records	Array of SubIdStatisticsRecord	The single transactions matching the search criteria

SubIdStatisticsRecord

Property	Type	Description
CheckDate	DateTime	Date when the transaction was checked
Commission	Decimal	Absolute monetary value of this transaction, regardless of the TransactionStatus
Confirmed	Decimal	Monetary value of this transaction, if it was confirmed
Date	DateTime	Date of the calculation
Number	Integer	A unique identifier, which helps us to identify this order, in case the publisher has questions about it.
Price	Decimal	If a sale was done on the advertiser's platform, this is the value of the sale
ProgramId	Integer	ID of the advertiser
ProgramTitle	String	Name of the advertiser
SubId	String	The evaluated subID
Transaction	String	Type of transaction. Possible values are: <ul style="list-style-type: none"> • L = Lead • S = Sale
TransactionStatus	Enumeration	Depicts the status of the sale or lead. Possible values are: <ul style="list-style-type: none"> • Open • Confirmed • Cancelled • All